# smiths medical bringing technology to life

## **Digit® Finger Pulse Oximeter**



The BCI® Digit® Finger Pulse Oximeter delivers fast, reliable oximetry in an extremely handy, pocket-size solution by combining the monitor and sensor into one unit. While it's small in size, Digit® is big on performance, providing SpO<sub>2</sub>, pulse rate, and pulse strength measurements for patients from pediatric to adult. This affordable, non-invasive device offers the convenience clinicians appreciate in EMS, hospital or clinical environments, as well as home use.

For more information, visit smiths-medical.com/bci.

**PATIENT MONITORING** 





### Digit® Finger Pulse Oximeter

- Combines monitor and sensor into one lightweight, pocket-size, portable solution.
- Easy-to-use, one-button keypad.
- Provides fast, reliable SpO<sub>2</sub>, pulse rate and pulse strength measurements.
- Monitor patients ranging from pediatric to adult.
- Large LED display for use in a wide range of light or dark environments.

- Auto power shutdown after 8 seconds conserves batteries when not in use.
- Low-battery indicator flashes when remaining battery time drops under 30 minutes.
- Rugged design features four springs enclosed in a high impact polycarbonate shell

#### **Technical Specifications**

#### **DISPLAYS, INDICATORS AND KEYS**

• SpO<sub>2</sub>

LED numeric display, 0.32 inches (8.1 mm) high

Pulse Rate

LED numeric display, 0.32 inches (8.1 mm) high

• Pulse Strength

LED bar graph display 0.32 inches (8.1 mm) high

• **Keys** On key

#### SPO<sub>2</sub>

Range

0 to 99% functional SpO<sub>2</sub> (1% increments)

• Accuracy

±2% at 70 to 99% less than 70% unspecified

• Averaging

8 pulse beat average

#### **PULSE RATE**

Range

30 to 254 bpm (1 bpm increments)

Accuracy

±2% or 2 bpm (whichever is greater)

Averaging

8 second average

#### **POWER REQUIREMENTS**

(2) "AAA" alkaline batteries (IEC Type LR03)

#### **BATTERY LIFE**

16 hours continuous use 1400 spot checks, 1 min ON, 2 min OFF

#### **DIMENSIONS**

2.25" H x 1.7" W x 1.5" D (5.72 cm H x 4.33 cm W x 3.81 cm D)

#### WEIGHT

3 oz. (85 grams) with batteries

#### **ENVIRONMENTAL**

- Operating Temperature 32°F to 131°F (0°C to 55°C)
- Storage Temperature -40°F to 167°F (-40° to 75°C)
- Relative Humidity (non-condensing) 10 to 95% (storage) 15 to 95% (operating)

#### **STANDARDS**

EN60601-1 (IEC60601-1) CAN/CSA 601.1 CAN/CSA NRTL/C)

#### REGULATORY COMPLIANCE

ISO 9001/ISO 13485

#### **CATALOG NUMBER**

3420Y

Digit® Finger Pulse Oximeter, Yellow

Information subject to change without notice. Please read the Instructions for Use supplied with the product for detailed instructions, warnings and cautions.
Q-Line for U.S.A. customers: call 1-800-348-1842 for clinical application information.

For more information, please call Smiths Medical PM, Inc., at 262-542-3100 or 800-558-2345, or your Smiths Medical distributor.

#### Smiths Medical PM, Inc.

Patient Monitoring and Ventilation

N7W22025 Johnson Drive, Waukesha, Wisconsin 53186 USA

Phone: 262-542-3100 Fax: 262-542-0718 Toll-Free: 800-558-2345

www.smiths-medical.com/bci

Smiths Medical, part of the global technology business Smiths Group

BCI, Digit and the Smiths Medical design mark are trademarks of the Smiths Medical family of companies. The symbol ® indicates the trademark is registered in the U.S. Patent and Trademark Office and certain other countries. All other names and marks mentioned are the trade names, trademarks or service marks of their respective owners. ©2008 Smiths Medical family of companies. All rights reserved. BCI 3420 Rev.03 05/08

smiths medical